



Note :  
 Source Resolution UXGA:  
 7680x4320 @60Hz  
 3840x2160 @120HZ

Specification :

- 1. Cabe UL20276, (1P(32AWG)+AL/MY)\*5 + 3C(32AWG) + 1C(28AWG) + 2C(24AWG) + AL+BD, Jacket Color: Black, OD: 4.6±0.15 mm
- 2. Conn. USB Type C Plug, Conductor: Gold Plated, Shell: Nickel Plated
- 3. Conn. DisplayPort Plug, Conductor: Gold Plated, Shell: Nickel Plated
- 4. Hood For USB Type C Plug, ABS, Color: Black
- 5. Hood For DisplayPort Plug, ABS, Color: Black
- 6. Inner molding LDPE
- 7. S.R. Black PVC: 45P

Part No.	Length	Resistance
11.04.5835	1000 mm	2 ohm
11.04.5836	2000 mm	2 ohm
11.04.5837	3000 mm	2 ohm

<b>SECOMP</b>	Product Name	ROLINE Adaptercable USB Type C-DP, v1.4(8K60Hz), M/M	Approve	Check	Draw	Design	Rev.	Date	Contents of Change	Design
	Product No.	11.04.5835/11.04.5836/11.04.5837	Allen	Allen	Kuan	Kuan	1			
Issue Date : 2020/11/05			Scale 1:1		Unit : mm		2			
			⊕				3			