



PIN OUT

P1 (TYPE C/M)		P2 (VGA/M-PCBA)
GND	DRAIN	OPEN
A3	BLUE	OPEN
A2	WHITE	OPEN
GND	DRAIN	OPEN
B10	GREEN	OPEN
B11	WHITE	OPEN
GND	DRAIN	GND
B3	RED	B3
B2	WHITE	B2
GND	DRAIN	GND
A10	BROWN	A10
A11	WHITE	A11
A8	GREY	A8
B5	YELLOW	B5
A7	GREEN	A7
A6	WHITE	A6
B8	PURPLE	B8
A5	ORANGE	A5
PWR	RED	PWR
SHELL	BRAID	SHELL

ITEM NO.	Length
11. 99. 5822	3000 ± 50mm
11. 99. 5821	2000 ± 30mm
11. 99. 5820	1000 ± 20mm

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
⑨	DUST CAP	LD-PE	1	
⑧	THUMB SCREW	#4-40 Nickel PLATED MATERIAL SCREW, Ø3.95MM*L52.7MM, MOLDING BLACK	2	
⑦	HOUSING	ABS Black	1	
⑥	OUTER MOLD	PVC Black	1	
⑤	INNER MOLD	LD-PE	2	
④	PCBA	Type C to VGA PCBA	1	
③	VGA	VGA 15P/M SOLDER TYPE, BLUE INSULATION The pin gold Plating,the Shell Gold Plating+PCB	1	
②	USB C TYPE	USB C /M Solder Type,Black PBT Insulation,The Pin Gold Plating, the shell for Gold Plating	1	
①	CABLE	USB3.1-C CABLE (32#T*1P+D+AL+HM) *4P+32#T*1P+32#T*4C+24#T*2C+AB PVC/Black Jacket OD:4.5±0.2MM	1	

NOTE:

100% DELL MAC BOOK HDTV TEST 1920×1080@60Hz
 Operating Temperature:0°C~45°C
 Storage Temperature:-20°C~ 70°C
 USB Type C male input
 VGA male output
 ROHS 2.0 and Reach compliant.

ITEM NO.	DESC.
11. 99. 5822	VALUE Adaptercable USB Type C-VGA, M/M, 3m
11. 99. 5821	VALUE Adaptercable USB Type C-VGA, M/M, 2m
11. 99. 5820	VALUE Adaptercable USB Type C-VGA, M/M, 1m

NEW		2018. 06. 01	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE

